



Grinders




Automatic Fresh and Frozen Meat Grinders Models W-160 & W-130

Both machines designed for Fresh or Frozen meats down to -16C!

Advantages:

- Stainless Steel Construction
- Easy to use HMI
- Dual auger system for feeding and grinding
- Adjustable speed for feeding and grinding
- Hopper design prevents sticking
- Safety Interlocks on front and top of machine
- Motors overload protected
- Built in Operator platform
- Machine prices include augers and sets for both Fresh and Frozen meats
- Equipment storage cart for cutting devices and auger
- Auger removal tool



Corporate Office
2899 Dowd Drive
Santa Rosa, CA 95407
707-523-5940



Blentech
corporation

Sales Office
232 Thurston Lake Dr.
Columbus, MS 39701
662-328-2750

www.blentechprocesssystems.com • www.blentech.com

Options for Blentech Grinders:

- Hydraulic Ejector of Feeding Screw
- Cutting set for Fresh Meats
- Special knife for frozen meat and skins
- Buggy lifts (Standard tubs)
- Attachment for tendon separation
- Attachment for mechanical separation of chicken



Features

	W-130	W-160
Diameter of grinder plate	5" / 130mm	6 1/4" / 160mm
Hopper Capacity (Est.)	300 lbs / 136 Kg	400 lbs / 182 Kg
Grind Auger Speeds	220 /440	150 /300
Feed Auger Speed - rpm	3 to 20 variable	3 to 20 variable
Maximum Output per Hour (lbs / kg) Fresh meat 39F / +4C *	6,600 lbs / 3,000 Kg	18,700 lbs / 8,500 Kg
Maximum Output per Hour (lbs / kg) Frozen meat 0F / -18C* **	2,850 lbs / 1,300 Kg	5,060 lbs / 2,300 Kg
Plate Sizes Available	3mm (1/8) 5mm (3/16) 8mm (5/16) 13mm (1/2) 20mm (3/4)	3mm (1/8) 5mm (3/16) 8mm (5/16) 13mm (1/2) 20mm (3/4)
Supply Voltage & Frequency at 60 Hz***	460v / 3ph*	460v / 3ph*
Installed Power (hp/Kw)	31.5 hp / 23 Kw	30/50 hp / 25/34 Kw
Length (in / mm)	58" / 1473	69" / 1750
Width (in / mm)	60" / 1510	98" / 2490
Height (in / mm?)	57" / 1450	75" / 1905
Weight (lbs / Kg)	2,150 lbs / 977 Kg	2,100 lbs / 955 Kg



* Through puts of meat depending on plate size

** Frozen meats with process assistance of meat flaker

*** Possibility of using other voltage and frequency upon order

Manufactured by Metalbud-Nowicki and sold in North America exclusively by Blentech Corporation.

Corporate Office
2899 Dowd Drive
Santa Rosa, CA 95407
707-523-5940



Blentech
corporation

Sales Office
232 Thurston Lake Dr.
Columbus, MS 39701
662-328-2750

www.blentechprocesssystems.com • www.blentech.com