

# TILTING VACUUM TUMBLERS

Blentech Vacuum Tilting Tumblers are designed to improve yield and texture for the production of high quality products. Perfect for the most sensitive and delicate products



- Solid Stainless Steel Construction
- Microprocessor control for operation of machines, monitoring of programs and performance
- Adjustable angle of tilting of tumbler
- Adjustable program parameters
- Possible for automated loading of one or multiple tumblers
- Dual ports for vacuum loading or viewing
- Optional load cell weight system
- Brine induction valve
- #4 Polished finish STANDARD
- Patented Blentech Wave Vane design shortens massaging time, gentle design means less destruction of product



Through incorporation of the patented **BLENTÉCH WAVE VANE** design increased movement of product from front to back of the tumbler is achieved while the drum turns. This action folds product over itself to assure even massaging and marinating. It's gentle nature will massage product without destruction of muscle or fiber. This action develops better appearance of the product, increased yield and better texture. The tilt feature allows the operator to find just the right combination of parameters for optimization of each individual product, faster, gently and effortlessly.



**Corporate Office**  
2899 Dowd Drive  
Santa Rosa, CA 95407  
707-523-5940



**Blentech**  
corporation

**Sales Office**  
232 Thurston Lake Dr.  
Columbus, MS 39701  
662-328-2750

[www.blentechprocesssystems.com](http://www.blentechprocesssystems.com) • [www.blentech.com](http://www.blentech.com)

## Two styles and three models to choose from

### MAH-PS

Designed for the processor who does not need refrigerated jacketing while processing



### MAH-PSCH

Designed for those special needs of chilling while tumbling to increase yield while maintaining temperature



Features	MAH-3200 PSCH	MAH-5200 PSCH	MA-7200 PSCH
MAXIMUM LOAD - Lbs	3,200	5,200	7,200
DRUM SPEEDS - RPM	0-10	0-8	0-7
OBTAINABLE VACUUM	95%	95%	95%
VOLTAGE* - 3 Phase	460	460	460
POWER RATINGS - HP/kW	15/11.2	20/13	25/15
CHILLER UNIT	ZCh-3	ZCh-3	ZCh-4
DIMENSIONS LxWxH (in/mm)	165x77x111 4200x1960x2820	175x85x120 4450x2150x3050	190x90x130 4800x2300x3300

Specifications subject to change without notice. \*Voltages can be selected at time of order.

**Corporate Office**  
2899 Dowd Drive  
Santa Rosa, CA 95407  
707-523-5940



**Blentech**  
corporation

**Sales Office**  
232 Thurston Lake Dr.  
Columbus, MS 39701  
662-328-2750

[www.blentechprocesssystems.com](http://www.blentechprocesssystems.com) • [www.blentech.com](http://www.blentech.com)